



KGS-SOHO-8-B



8-Port 10/100/1000Base-T Gigabit Ethernet Switch

Key Features:

- Provides 8 10/100/1000Mbps Gigabit Ethernet ports
- All 10/100/1000M ports support auto-negotiation and auto-MDI/MDI-X detection
- Supports full/half-duplex transfer mode for 10/100Mbps
- Supports full-duplex transfer mode for 1000Mbps
- Store-and-Forward switching method
- Wire-speed packet filtering and forwarding rate
- Supports IEEE 802.3x flow control
- Supports jumbo frame up to 9K bytes
- Supports 802.1p QoS classification

Specifications:

Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x
Network Ports	8 10/100/1000Mbps Gigabit copper ports Shielded RJ-45, auto-negotiation, auto-MDI/MDI-X support
Network Cables	10Base-T: Cat.3, 4, 5 or higher (100 meters max.) 100Base-TX: Cat.5, 5e or higher (100 meters max.) 1000Base-T: Cat.5e or higher (100 meters max.)
Network Data Rate	Ethernet: 10Mbps (Half-duplex) 20Mbps (Full-duplex) Fast Ethernet: 100Mbps (Half-duplex) 200Mbps (Full-duplex) Gigabit Ethernet: 2000Mbps (Full-duplex)
MAC Address Table	4K entries
Buffer Memory	1.5M bits
LED Indication	Per unit: Power Per port: link/activity status
Environment	Operating Temperature: 0°C ~ 40°C Storage Temperature: -20°C ~ 70°C Relative Humidity: 10% ~ 90% non-condensing
Dimension	155 x 85 x 26 mm (WxDxH)
Power Input	+5V via external power adapter
Power Consumption	3.5W max. @+5V (DC IN)
Approval	FCC Class B, CE mark Class B



Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-chih District, New Taipei City, Taiwan
Tel: 886-2-2698-3878
Fax: 886-2-2698-3873
E-mail: kti@ktinet.com.tw
URL: http://www.ktinet.com.tw

KTI Networks Inc.

10415-A Westpark Drive, Houston,
TX 77042. U.S.A.
Tel: 1-713-266-3891
Fax: 1-713-914-0555
E-mail: contact@ktinet.com
URL: http://www.ktinet.com

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.
This information is subject to change without prior notice.